

EVERSTAR industries

Driven by Vision. Powered by Strength.

www.everstarindustries.com



ENGINE	
Make	Weichai Euro 2 Turbo charged Intercooled
Model Configuration	WP 10.340 E32
Max Power—Kw @ r/min	250/2200
Max Torque—N.m @ r/min	1350/1200-1600
HP	340
Cylinder	6 Inline
Water Cooled	A
Direct Injection	A
Engine driven P.T.O	Yes
Displacement (I)	9.726
Compression Ratio	17:01

BRAKES	
Service	Double circuit air brakes
Emergency / Parking	Spring potential brake
Auxiliary	ABS & EVB

STANDARD TYRE EQUIPMENT	
Size and ply rating	315x80R22.5 incl spare wheel

FRUNT AXLE	
Туре	VR4/01D-7.5
Suspension	Non-free standing stabilization leaf spring, hydraulic shock absorber, transverse stabilizer

MIDDLE & REAR AXLE	
Туре	HD7/016DGS - HL7/015DS-13/4.796
Suspension	Stabilizator suspension, 13 pcs leaf spring (each 20mm)
	Hub reduction ayles

ELECTRICAL EQUIPMENT	
Alternator	70Amp
Starter Motor	5.58kW
Batteries	2 x 12V — 120AH

PERFORMANCE DATA	
Gradeability @ GVM	30% @ GVM
Max Geared Road Speed	90km/h (Limited to 80km/h)
Final Drive Ratio	4.769

CLUTCH	
Make / Type / Size	GFX 430mm single
Operation	Single dry frictional disc, diaphragm spring, pulling type

WAKKANIY	
New Vehicle	3 years / 300 000km (SA only)
	T&C comply. Please refer to warranty booklet.

TRANSMISSION	
Make/Model	12JS200T+QH50
No of Gears	12
Synchromesh or Constant Mesh	Synchromesh
P.T.O	Yes

RATIO			
Crawler		7th	3.48
1st	15.53	8th	2.71
2nd	12.08	9th	2.10
3rd	9.39	10th	1.64
4th	7.33	11th	1.28
5th	5.73	12th	1.00
6th	4.46	Reverse L	14.86
		Reverse H	3.33

DIMENSIONS		
Overall Length (OL)	9 400	
Overall Width (OW)	2 495	
Overall Height (OH)	3 085	
Front Overhang (FOH)	1 435	
Rear Overhang (ROH)	1 350	
Wheel Base (WB)	5 025	
Bumper to Back of Cab (BBC)	2 215	
Cab to rear axle / unit (CA)	5 040	
Turning Radius (TR)	11 500	
Fuel Tank Capacity	4001	

MASS INFORMATION	
Manufacturers Gross Vehicle Mass (GVM)	40 000
Manufacturers Gross Combination Mass (GCM)	75 000
Manufacturers Front Axle mass (GA)	15 000
Manufacturers Rear Axle mass (GAU)	26 000
Permissible Maximum Vehicle Mass (V)	31 650
Permissible Maximum Front Axle Mass (AF)	15 000
Permissible Maximum Rear Axle Mass (AR)	18 000
Unladen Front Axle Mass (UF)	5 880
Unladen Rear Axle Mass (UR)	4 260
Total Unladen Mass (UT)	10 140
Permissible Max Drawing Vehicle Mass (D/T)	60 000

CAB (Day Cab)	
Hydraulic Tiltable Cab	















Comments:

Visit www.everstarindustries.com for dealer network

Please note: The manufacturer reserves the right to make changes to the design, form, colour and specifications of any Powerstar brochure without notice. The picture shown is for illustrated purposes only.



